



2nd Gen C Series

Designed for Cabinet Embedded Applications

Embedded ARM All-in-One Panel PC



Panel-mount Wall-embedded Wall-mounted Desktop Folding mounting VESA mount Ceiling-mounted



E-mail: touchtec@sztouchtec.com
 Website: www.touchtecs.com
 Shenzhen Touch Think Intelligence Co., Ltd.



Embedded ARM All-in-One Panel PC



(Here take the RK3288 motherboard-based panel PC for your reference)



Pure flat frame, dustproof and waterproof. efficient cooling structure design



Self-developed RK3288 high-performance motherboard



High-precision aluminum alloy material



Diverse expandable interfaces

10.1/10.4/11.6/12/12.1/13.3/15/15.6/17/17.3/19/19.1/21.5/23.8 inch are available and optional, more sizes can be customized.

Basic Parameters	CPU	RK3288 Cortex-A17 Quad Core 1.8GHz	RK3399 Six Core 64 Bit 1.8GHz	
	Memory	2GB DDR3 (8GB optional)	4GB DDR3 (8GB optional)	
	Storage	16GB eMMC (32GB optional)	32GB eMMC (64GB optional)	
	GPU	Mali-T764	Mali-T860MP4	
	OS	Android 7.1/10.0/12.0, Linux4.4/Ubuntu18.04/Debian10.0	Android 7.1/9.0/11, Ubuntu18.04/Debian10.0/Linux4.4+QT	
	Bluetooth	Support	Support	
	WiFi	Support dual band wifi	Support dual band wifi	
	Power input	12V power input	12V-36V power input	
	Touch Screen	Capacitive Touch Touch screen type: 10 point touch projection capacitive touch screen Light transmittance: ≥ 88% Input mode: handwriting or capacitive pen Controller communication: USB		Resistive Touch Touch screen type: single point resistive touch screen Light transmittance: ≥ 78% Input mode: Fingertip or stylus Controller communication: USB
		Non-touch Light transmittance: ≥ 92%		
Other Parameters	Operation temperature	-10 °C ~ 60 °C	Storage temperature	-20 °C ~ 70 °C
	Mechanical	Material: aluminum alloy, color: black, silver optional		
	Installation method	Supports embedded mount, panel-mount, wall-hanging, desktop, folding mounting, VESA mount, adjustable ceiling mounted, and open frame, etc.		