



2nd Gen I Series

Designed for Cabinet Embedded Applications

Embedded X86 All-in-One Panel PC



Panel-mount Wall-embedded Wall-mounted Desktop Folding mounting VESA mount Ceiling-mounted



E-mail: touchtec@sztouchtec.com
 Website: www.touchtecs.com
 Shenzhen Touch Think Intelligence Co., Ltd.



Embedded X86 All-in-One Panel PC



(Here take the I5 motherboard-based panel PC for your reference)

- Rugged high-performance CPU
- Embedded installation and IP65 dustproof and waterproof
- Fanless design for better heat dissipation
- Multiple OS

10.1/10.4/11.6/12/12.1/13.3/15/15.6/17/17.3/19/19.1/21.5/23.8 inch are available and optional, more sizes can be customized.

Basic Parameters	CPU	Intel I3-6100U/I3-8145U/I3-10110U	I5-6200U/I5-7200U/I5-8265U/I5-10210U	Intel I7-6500U/I7-7500U/I7-8565U/I7-10510U
	Memory	4GB DDR4 (8GB optional)	4GB DDR4 (8GB optional)	4GB DDR4 (64GB optional)
	Storage	128GB SSD(256GB/512GB optional)	128GB SSD(256GB/512GB optional)	128GB SSD(256GB/512GB optional)
	Integrated Graphics	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics
	OS	Win7/10/11,Ubuntu/Centos	Win7/10/11,Ubuntu/Centos	Win7/10/11,Ubuntu/Centos
	WiFi	Support dual band wifi	Support dual band wifi	Support dual band wifi
	Power Input	12V-36V power input	12V-36V power input	12V-36V power input
Touch Screen	Capacitive Touch Touch screen type: 10 point touch projection capacitive touch screen Light transmittance: ≥ 88% Input mode: handwriting or capacitive pen Controller communication: USB		Resistive Touch Touch screen type: single point resistive touch screen Light transmittance: ≥ 78% Input mode: Fingertip or stylus Controller communication: USB	
	Non-touch Light transmittance: ≥ 92%			
Other Parameters	Operation Temperature	-10 °C ~ 60 °C	Storage Temperature	-20 °C ~ 70 °C
	Mechanical	Material: aluminum alloy, color: black, silver optional		
	Installation Method	Supports embedded mount, panel-mount, wall-hanging, desktop, folding mounting, VESA mount, adjustable ceiling mounted, and open frame, etc.		